


DS-3E05-E Series Unmanaged Gigabit Switch

Features and Functions



DS-3E0508-E

- I Compliant with IEEE802.3, IEEE802.3u, IEEE802.3ab Ethernet standard
- I 8*10/100/1000Mbps auto-negotiation RJ45 Ports
- I Plug and play without configuration
- I Up to 16 Gbps back panel bandwidth and supports non-blocking wire-speed forwarding
- I LEDs to easily monitor link speed, activity and find problems in time
- I IEEE802.3x full duplex flow control and half duplex backpressure flow control
- I Loop detection and loop prevention
- I Up to 4 kV lightning-proof for each port
- I Desk & wall-mounting installation.
- I Full-metal & larger shell ensure effective cooling

DS-3E0516-E & DS-3E0524-E

- I Compliant with IEEE802.3, IEEE802.3u, IEEE802.3X, IEEE802.3ab Ethernet standards
- I 16/24*10/100/1000Mbps auto-negotiation RJ45 ports
- I Auto MDI/MDIX
- I 8K MAC address and MAC address learning
- I IEEE 802.3x full duplex flow control, and Backpressure half duplex flow control
- I 32 Gbps/48 Gbps backplane bandwidth for non-blocking line-speed forwarding
- I LED indicators for indicating working status and troubleshooting
- I Built-in power supply system with 4000V common mode and 4000V differentiate mode lightning immunity
- I 1U standard height suitable for desktop and rack installation
- I Ports all with 4000V common mode lightning immunity
- I IP camera connection




Specifications

Specifications				
Product Model		DS-3E0508-E	DS-3E0516-E	DS-3E0524-E
Network Standard		IEEE 802.3, IEEE 802.3u, IEEE802.3ab, IEEE 802.3x		
Transmission Speed		Ethernet: 10 Mbps (Half Duplex) / 20 Mbps (Full Duplex) Fast Ethernet: 100 Mbps (half-duplex)/200 Mbps (full-duplex) Gigabit Ethernet: 2000 Mbps (full-duplex)		
Transmission Medium		Ethernet: CAT3 or better UTP/STP cable Fast Ethernet: CAT5 or better UTP/STP cable Gigabit Ethernet: CAT5E or CAT6 UTP/STP cable (recommended)		
Ports		8*10/100/1000Mbps auto-negotiation RJ45 ports	16*10/100/1000Mbps auto-negotiation RJ45 ports	24*10/100/1000Mbps auto-negotiation RJ45 ports
Port Type	Port loopguard	Supported		
	Uplink port	Port 8	Port 15 and Port 16	Port 23 and Port 24
Lightning-proof Ranking	RJ45 port	4 kV	4 kV	
	Power source	2 kV	4 kV	
LED Indicator		1 * power LED 8 * Link/Act LED	1 * power LED 16 * Link/Act LED	1 * power LED 24 * Link/Act LED
Dimensions (L*W*H)		186.7mm×106.7mm× 33.3mm	440mm×178.8mm×44mm	
Store-and-forward		Supported		
MAC address table		4 k	8 k	
MAC address learning		Automatic learning/Aging		
Package filtering/Forwarding rate		Ethernet: 14881 pps one port Fast Ethernet: 148810 pps one port Gigabit Ethernet: 1488100 pps one port		
Backplane bandwidth		16 Gbps	32 Gbps	48 Gbps
Power supply		Input: 100-240 V AC, 50/60 Hz, 0.3 A Output: 9 V DC, 1 A	Input: 100-240 V AC, 50/60 Hz	
Operating temperature		0°C - 40°C		
Operating humidity		(10-90) % RH, non-condensing		
Storage temperature		-40°C – 70°C		
Storage humidity		(5-90) % RH, non-condensing		


Appearance

Front Panel




DS-3E0508-E

Index	Description	Index	Description
1	Power LED Indicator	2	Link/Act LED Indicator



DS-3E0516-E


Index	Description	Index	Description
1	Power LED Indicator	3	RJ45 Port
2	Link/Act LED Indicator		



DS-3E0524-E


Index	Description	Index	Description
1	Power LED Indicator	3	RJ45 Port
2	Link/Act LED Indicator		

Rear Panel



DS-3E0508-E

Index	Description	Index	Description
1	RJ45 Port	2	Power Jack



DS-3E0516-E & DS-3E0524-E

Index	Description	Index	Description
1	Grounding Terminal	2	Power Jack

Distributed by



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Europe
T +31-23-5542770
saleseuro@hikvision.com

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision France
T +33(0)1-85-330-444
info.fr@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision UK
T +44-1628-9021-4
support.uk@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com